

# Rite Way Jumbo Harrows Specifications



7100 Model #	JH7128	JH7140	JH7150	JH7162	JH7173
Working Width	28'	40'	50'	60'	73'
Harrow sections	3 1-6' 6", 2-11'	5 3-6' 6", 2-11'	5 1-6' 6", 4-11'	7 3-6' 6", 4-11'	7 1-6' 6", 6-11'
6 1/2" section tines*	15 double tines/ 2-3/4" tine spaces	15 double tines/ 2-3/4" tine spaces	15 double tines/ 2-3/4" tine spaces	15 double tines/ 2-3/4" tine spaces	15 double tines/ 2-3/4" tine spaces
11' section tines*	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces
Tine adjust	hydraulic over mechanical	hydraulic over mechanical	hydraulic over mechanical	hydraulic over mechanical	hydraulic over mechanical
Draft arm	solid pull	solid pull	solid pull	solid pull	solid pull
Knuckle pins	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"
Transport width*	9' 6"	9' 6"	9' 6"	9' 6"	9' 6"
Transport height*	11' 4"	11' 4"	11' 4"	11' 4"	11' 4"
Transport length*	30'	37'	41'	47'	54'

8100 Model #	JH8133	JH8145	JH8155	JH8168	JH8178	JH8190
Working Width	33'	45'	55'	68'	78'	90'
Harrow sections	3 3-11'	5 3-11', 2-6 1/2'	5 5-11'	7 5-11', 2-6 1/2'	7 7-11'	9 7-11', 2-6 1/2'
6 1/2" section tines*		15 double tines/ 2-3/4" tine spaces		15 double tines/ 2-3/4" tine spaces		15 double tines/ 2-3/4" tine spaces
11' section tines*	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces	25 double tines / 2-3/4" tine spaces
Tine adjust	Hydraulic over mechanical	Hydraulic over mechanical	Hydraulic over mechanical	Hydraulic over mechanical	Hydraulic over mechanical	Hydraulic over mechanical
Draft arm	solid pull	solid pull	solid pull	solid pull	solid pull	solid pull
Knuckle pins	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"
Transport width*	14'7"	14'7"	14'7"	14'7"	14'7"	17'
Transport height*	14'11"	14'9"	14'9"	14'9"	14'5"	16'3"
Transport length*	35'	41'	45'	52'	57'	65'10"

Standard Equipment: 40° to 85° Hydraulic tine angle adjust from tractor cab, 9/16" x 26" harrow tines, 5 bar/18" spacing between rows/ 2 3/8" diameter pipe mechanical auto fold, hydraulic transport/field pivot wheel system, self-leveling parallel linkage, spring adjustable harrow down pressure, adjustable hitch height c/w perfect hitch clevis, 16.5L x 16.1 flotation tires on main frame, 11L x 15 highway service tires on wings, 8" x 8" x 1/4" wall HS tube on wing and center bar, 8 x 4 x 3/16" wall HS tube on the A-frame, safety chain.

Optional Equipment: acre meter, Valmar granular applicator, lighting kit.

\*approximate measurements

Because we are constantly striving to improve our products, we reserve the right to change the design, materials and specifications without notice.