

Rite Way Rockpicker / Windrower Specifications



Rockpickers	RR250ST	RR900ST
Drive	Variable Hydraulic Drive	Variable Hydraulic Drive
Reel	2 Bat	3 Bat
Reel Chain	#80	#80
Picking Width	50"	60"
Minimum Rock Diameter	2"	2"
Maximum Rock Diameter	24"	32"
Bucket Capacity	1.75 Cubic Yards	2.6 Cubic Yards
Reel & Bucket Control	Electric over Hydraulic	Electric over Hydraulic
Weight Capacity	3,600 lbs. (1650 Kg)	8,000 lbs. (4500 Kg)
Dumping Height	48"	60"
Tires	12.5L x 15	16.5 x 16.1
Hitch	Multi-Position (Standard) Hydraulic Swing (Optional)	Multi-Position (Standard) Hydraulic Swing (Optional)
Hydraulic Requirements	12 - 15 gal/min. @ 1200 - 1500 PSI	12 - 15 gal/min. @ 1200 - 1500 PSI
Rock Windrowers	RW850	RW1200
Working width	254 cm / 110"	373 cm / 144"
Height		812 mm / 32"
Weight	368 kg. / 810 lbs.	520 kg / 1150 lb.
Drive	Hydraulic	Hydraulic
Transport Height		1066 mm / 42"
Transport Length	203 cm / 80"	381 cm / 107"
Transport Width	292 cm / 115"	360 cm / 142"

Because we are constantly striving to improve our products, we reserve the right to change the design, materials and specifications without notice.