

F-3 LAND ROLLER SPECIFICATIONS



Model	# of Segments	Drum Diameter	Drum Thickness*	Wing Configuration	Transport Width	Transport Length	Weight*	Frame	Tires
F3-32	3	42" / 107cm	0.50" (1.3cm)	10'-12'-10' 3.1m-3.6m-3.1m	14' / 4.3 m	38' / 11.6m	17,640 lbs (8,100 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	11L x 15 - 8 ply
F3-36	3	42" / 107cm	0.50" (1.3cm)	12'-12'-12' 3.6m-3.6m-3.6m	14' / 4.3 m	40' / 12.2m	19,000 lbs (8,618 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	11L x 15 - 8 ply
F3-42	3	42" / 107cm	0.50" (1.3cm)	15'-12'-15' 4.5m-3.6m-4.5m	14' / 4.3 m	45' / 13.7m	21,220 lbs (9,625 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	11L x 15 - 8 ply
F3-46	3	42" / 107cm	0.50" (1.3cm)	17'-12'-17' 5.2m-3.6m-5.2m	14' / 4.3 m	47' / 14.3m	22,910 lbs (10,391 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	12.5L x 15 - 8 ply
F3-52	3	42" / 107cm	0.50" (1.3cm)	20'-12'-20' 6.1m-3.6m-6.1m	14' / 4.3 m	50' / 15.2m	24,400 lbs (11,067 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	12.5L x 15 - 8 ply
F3-40NT	3	42" / 107cm	0.50" (1.3cm)	15'-10'-15' 4.5m-3.1m-4.5m	11' 6" / 3.5m	45' / 13.7m	20,600 lbs (9,344 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	11L x 15 - 8 ply
F3-44NT	3	42" / 107cm	0.50" (1.3cm)	17'-10'-17' 5.2m-3.1m-5.2m	11' 6" / 3.5m	47' / 14.3m	22,100 lbs (10,024 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	12.5L x 15 - 8 ply
F3-50NT	3	42" / 107cm	0.50" (1.3cm)	20'-10'-20' 6.1m-3.1m-6.1m	11' 6" / 3.5m	50' / 15.2m	23,100 lbs (10,478 kg)	3 section: 6" x 4" x .250" 15cm x 10cm x 0.64cm	12.5L x 15 - 8 ply

*approximate

We are continuously improving our products. Design, specifications and material are subject to change without notice.